# Safety Data Sheet

Date of issue: 07/29/2026 Revised On 07/29/2026

## 1 Identification of the substance and manufacturer

**Trade name:** **65-501 1752 DEEP BLUE**
**Other means of identification**

**Product code:** CBQA065501
**Article category**
**Recommended use:** Paint and coatings application.
**Uses advised against:** Any that differs from the recommended use.
**Manufacturer/Supplier:**

Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178 USA
phone: 815-895-9101
www.seymourpaint.com

Seymour of Sycamore
3041 Dougall Avenue, Suite 503
Windsor, ONT N9E 1S3 CANADA
phone: 800-435-4482
www.seymourpaint.com

**Emergency telephone number:** 1-800-255-3924

## 2 Hazard(s) identification

**Classification of the substance or mixture**

| | | |
|---|---|---|
| Aerosols 1 | H222-H229 | Extremely flammable aerosol. Pressurized container: may burst if heated. |
| Skin irritation 2 | H315 | Causes skin irritation. |
| Eye irritation 2A | H319 | Causes serious eye irritation. |
| Carcinogenicity 2 | H351 | Suspected of causing cancer. Route of exposure: Inhalation. |
| Reproductive toxicity 2 | H361 | Suspected of damaging fertility or the unborn child. |
| Specific target organ toxicity (single exposure) 3 | H336 | May cause drowsiness or dizziness. |
| Specific target organ toxicity (repeated exposure) 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |

**Additional information:**
**GHS Hazard pictograms**

GHS02 GHS07 GHS08

**Signal word** Danger
**Hazard statements**
Extremely flammable aerosol. Pressurized container: may burst if heated.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer. Route of exposure: Inhalation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing fume/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Wear protective gloves.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store in a well ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures**
**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

| **Dangerous components:** | | |
|---|---|---|
| 67-64-1 | Acetone | 25-50% |
| 108-88-3 | Toluene | ≥15-<20% |
| 74-98-6 | propane | 15-25% |
| 106-97-8 | n-butane | 5-10% |
| 111-76-2 | Glycol Ether EB | 1-5% |

(Contd. on page 2)

# Safety Data Sheet

Date of issue: 07/29/2026 Revised On 07/29/2026

**Trade name: 65-501 1752 DEEP BLUE**

(Contd. of page 1)

| | | |
|---|---|---|
| 2807-30-9 | Glycol Ether EP | 1-5% |
| 108-65-6 | PM acetate | 1-5% |

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
**After swallowing:** Rinse mouth with water. Do not induce vomiting.
**Most important symptoms and effects:** Dizziness
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.
**Special hazards:** Can form explosive gas-air mixtures.
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.
**Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13.

## 7 Handling and storage

**Precautions for safe handling** Use only in well ventilated areas.
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

**Components with limit values that require monitoring at the workplace:**

| | |
|---|---|
| **67-64-1 Acetone** | |
| PEL (USA) | Long-term value: 2400 mg/m³, 1000 ppm |
| REL (USA) | Long-term value: 590 mg/m³, 250 ppm |
| TLV (USA) | Short-term value: 1187 mg/m³, 500 ppm<br>Long-term value: 594 mg/m³, 250 ppm<br>A4, BEI |
| **108-88-3 Toluene** | |
| PEL (USA) | Long-term value: 200 ppm<br>Ceiling limit value: 300; 500* ppm<br>*10-min peak per 8-hr shift |
| REL (USA) | Short-term value: 560 mg/m³, 150 ppm<br>Long-term value: 375 mg/m³, 100 ppm |
| TLV (USA) | Long-term value: 20 ppm<br>BEI, OTO, A4 |
| **74-98-6 propane** | |
| PEL (USA) | Long-term value: 1800 mg/m³, 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m³, 1000 ppm |
| TLV (USA) | see Appendix F Minimal oxygen content ( D, EX) |
| **106-97-8 n-butane** | |
| REL (USA) | Long-term value: 1900 mg/m³, 800 ppm |
| TLV (USA) | Short-term value: 2370 mg/m³, 1000 ppm<br>(EX) |
| **111-76-2 Glycol Ether EB** | |
| PEL (USA) | Long-term value: 240 mg/m³, 50 ppm<br>Skin |
| REL (USA) | Long-term value: 24 mg/m³, 5 ppm<br>Skin |
| TLV (USA) | Long-term value: 97 mg/m³, 20 ppm<br>BEI, A3 |
| **108-65-6 PM acetate** | |
| WEEL (USA) | Long-term value: 50 ppm |

(Contd. on page 3)

# Safety Data Sheet

Date of issue: 07/29/2026 Revised On 07/29/2026

**Trade name: 65-501 1752 DEEP BLUE**

(Contd. of page 2)

| Ingredients with biological limit values: | |
|---|---|
| **67-64-1 Acetone** | |
| BEI (USA) | 25 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific) |
| **108-88-3 Toluene** | |
| BEI (USA) | 0.02 mg/L<br>Medium: blood<br>Time: prior to last shift of workweek<br>Parameter: Toluene<br><br>0.03 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Toluene<br><br>0.3 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: o-Cresol with hydrolysis (background) |
| **111-76-2 Glycol Ether EB** | |
| BEI (USA) | 200 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Butoxyacetic acid (BAA) (with hydrolysis) |

**Hygienic protection:** Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Store protective clothing separately.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

| | |
|---|---|
| **Physical state** | Aerosol |
| **Odor:** | Aromatic |
| **Odor threshold:** | Not determined. |
| **Melting point/Melting range** | Undetermined. |
| **Boiling point:** | -44.5 °C (-48.1 °F) |
| **Flammability:** | Extremely flammable. |
| **Lower Explosion Limit:** | 1.7 Vol % |
| **Upper Explosion Limit:** | 10.9 Vol % |
| **Flash point:** | -19 °C (-2.2 °F) |
| **Flammability (solid, gas):** | Extremely flammable. |
| **Decomposition temperature:** | Not determined. |
| **pH-value:** | Not determined. |
| **Viscosity:** | Not determined. |
| **Solubility:** | Not determined. |
| **Vapor pressure:** | Not determined. |
| **Relative Density:** | Between 0.77 and 0.85 (Water equals 1.00) |
| **Vapor density** | Not determined. |
| **Particle characteristics** | Not applicable. |
| **Appearance:** | Aerosol. |
| **Ignition temperature:** | Product is not self-igniting. |
| **Danger of explosion:** | In use, may form flammable/explosive vapour-air mixture. |
| **Water:** | 0.0 % |
| **Evaporation rate** | Not applicable. |
| **Partition coefficient: n-octonal/water:** | Not determined. |

## 10 Stability and reactivity

**Reactivity:** Stable at normal temperatures.

**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Chemical stability:** Not fully evaluated.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Incompatible materials:** No further relevant information available.

(Contd. on page 4)

# Safety Data Sheet

Date of issue: 07/29/2026 Revised On 07/29/2026

**Trade name: 65-501 1752 DEEP BLUE**

(Contd. of page 3)

**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

**LD/LC50 values that are relevant for classification:**

**111-76-2 Glycol Ether EB**

| | | |
|---|---|---|
| Oral | LD50 | 1,200 mg/kg (ATE) |
| | | 1,480 mg/kg (rat) |
| Dermal | LD50 | 400 mg/kg (rab) |
| Inhalative | LC50/4 h | 3 mg/l (ATE) |

**108-65-6 PM acetate**

| | | |
|---|---|---|
| Oral | LD50 | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat) |

**Information on toxicological effects:** No data available.
**Skin effects:** No irritant effect.
**Eye effects:** Irritating effect.
**Sensitization:** No sensitizing effects known.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
**Bioaccumulative potential:** No further relevant information available.
**Mobility in soil:** No further relevant information available.
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
**Recommendation:** Completely empty cans should be recycled.
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number** UN1950
**DOT** UN1950
**DOT** Aerosols, flammable
**ADR** 1950 AEROSOLS
**Transport hazard class(es):**
**Class** 2.1 Gases
**Special marking (IATA):**
**Packaging Group:** --
**Special precautions for user:** Warning: Gases
**EMS Number:** F-D,S-U
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

| | |
|---|---|
| 108-88-3 | Toluene |
| 111-76-2 | Glycol Ether EB |

**Toxic Substances Control Act (TSCA):** All ingredients are found on the inventory list of substances.
**Canadian Domestic Substances List (DSL):** All ingredients are listed or exempted.
**Consumer Product Safety Comission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

| | |
|---|---|
| 13463-67-7 | titanium dioxide |
| 1333-86-4 | Carbon black |

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

| | |
|---|---|
| 108-88-3 | Toluene |

**EPA:**

| | | |
|---|---|---|
| 67-64-1 | Acetone | I |

(Contd. on page 5)

# Safety Data Sheet

Date of issue: 07/29/2026 Revised On 07/29/2026

**Trade name: 65-501 1752 DEEP BLUE**

(Contd. of page 4)

| | | |
|---|---|---|
| 111-76-2 | Glycol Ether EB | NL |

## 16 Other information

**Contact:** Regulatory Affairs